

佶慶電機有限公司

CHESHIRE ELECTRIC COMPANY, LLC

Driver for Brushless Motor with Sensor 有感無刷馬達驅動器

MODEL OHS1-28V10A	DRIVER SPECIFICATIONS 驅動器規格書	Page: 1 OF 1
----------------------	---------------------------------	--------------



驅動器規格 Motor Driver Specifications

輸入電源 Input Voltage	DC9-28V
驅動電流 Operation Current	10A
驅動模式 Drive mode	Sine Wave Drive
感測器 Sensor	3 霍爾感測器。3 HALL Sensor
運轉功能 Operation Functions	1. 啟動/停止。Start/Stop
	2. 轉速調整。Speed control
	3. 正/反轉。Direction control CW/CCW
保護功能 Protections	<p>1. 電源逆接保護功能：輸入端電壓正負極接反時，馬達無法運轉。 1. Polarity Protection: If power polarity error, the motor can not been operated.</p> <p>2. 馬達限電流功能：馬達瞬間最大限電流20A。 2. Pulsed Current Limit: The motor pulsed current limit is 20A .</p> <p>3. 過溫保護：驅動IC溫度超過160°C 停止工作，直到驅IC驅動器降到150°C 以下，重新供電恢復正常工作。 3. Temperature Protection: If the temperature of the driver IC is Over 165°C, it will be shut down. Once all the driver board components' temperature drop below 150°C, restart the power.</p>
工作溫度 Operating Temperature	- 10°C~60°C
外型尺寸 Size	126x66x28mm
重量 Weight	172g

驅動器面板功能說明 Instructions for use

No.	Function	SW-1234	NO.	Function
1	Hall_+5V		1	NC
2	Hall_U		2	NC
3	Hall_V		3	start/stop
4	Hall_W		4	DIR
5	Hall_GND			
6	Start/Stop			
7	DIR			
8	NC			
9	NC			
10	GND			