



| CONNECTOR PIN LOCATION | | | | | |
|------------------------|--------|--------------|---|---|---|
| PIN | COLOR | ← CCW → CW → | | | |
| 1 | BLACK | + | - | - | + |
| 2 | GREEN | - | + | + | - |
| 3 | RED | + | + | - | - |
| 4 | BLUE | - | - | + | + |
| 5 | YELLOW | | | | |
| 6 | WHITE | | | | |

註：以雙極性驅動板測試

| | | | | | |
|---|------|-----------|--------------------------------|-------------|---|
| THIRD ANGLE PROJECTION ALL DIMENSION ARE IN MM (UNLESS OTHERWISE SPECIFIED) | 製圖 | JOANNE | Cheshire Electric Company, LLC | | |
| | 設計 | | Part No JH57-E0G1A769 | | |
| 繪製比例: 1:1 | 審核 | | Name HB stepper motor | REV. NO. | B |
| | 材料 | | | | |
| | 完成時間 | 2012/9/14 | | | |

| MODEL | | Motor Characteristics | | | | | |
|------------------|--------------|-----------------------|------------|------------------|--------------|--------------|---------------|
| JH57-E0G1A769 | | Resistance | Step Angle | Steps Revolution | Max PIT Rate | Max POT Rate | POT(at400pps) |
| Constant current | 24V 0.4 A | 5.7Ω | 0.9 ° | 400 | 800PPS | 1000PPS | 4000g-cm |